

# PERFORMANCE SPECIFICATION HYDRA-BOY

## DELIVERY INCLUDES

Wasser- und Schlammsauger, elektronikfrei, zum kontinuierlichen Absaugen und Entsorgen von Flüssigkeiten, Schmutzwasser oder Ähnlichem. Leistung: mind. 230 V / 1,200 W, Behälter: mind. 45 l Fassungsvermögen, stabiles Fahrwerk mit Feststellbremse, kompakte Abmaße mit abnehmbarem Griff, Anschluss C-Storz-Kupplung, Wassersaugleistung regulierbar von 140-250 l/min, Schlürfbetrieb möglich, Edelstahl-Schmutzwasserpumpe 230 l/min, freier Korndurchgang 30 mm, max. Förderhöhe 8 m, trockenlaufsicher, automatisch-mechanische Abschaltung bei Erreichen des maximalen Behältervolumens, Personenschutzschalter.

Saugschlauch  $\varnothing$  50 mm, 10 m; Ablaufschlauch  $\varnothing$  50 mm, 10 m; 4-teiliges Saugrohr; Alu-Bodendüse 45 cm breit

## OPTIMAL ACCESSORIES

PRCD-S+ personal protection switch, ball valve with C-Storz-coupling, plug protection class IP 68

## TECHNICAL DATA HYDRA-BOY

Main voltage	220-240 V / 50 Hz
Socket	max. 1,600 W
Sound pressure level	82 db(A)
Suction capacity	8,000 l/h
Container material	Plastic PP
Container volume	45 Liter
Power cable length	10 m
Suction hose length	10 m
Drain hose length	10 m
Suction hose	$\varnothing$ 38 mm
Drain hose	$\varnothing$ 38 mm
Weight	18 kg
Size without handle (B x T x H)	46x49x64 cm
Size with handle (B x T x H)	46x66x85 cm



## TECHNICAL DATA TURBINE

Main voltage	220-240 V / 50 Hz
Turbine capacity	1,200 W
Volume flow / air volume	60 l/sec.
Max. vacuum	230 mbar

## TECHNICAL DATA PUMP

Main voltage	220-240 V / 50 Hz
Capacity waste water pump	900 W
Output pump	14,000 l/h
Discharge head, max.	8 m (0.8 bar)
Material	Plastic

Subject to technical changes, our terms and conditions apply: [www.roessle.ag](http://www.roessle.ag)

# rössle

Vacuum cleaners for fire departments