

PERFORMANCE SPECIFICATION HYDRA-BOY

DELIVERY INCLUDES

Water and mud vacuum cleaner, electronic-free, for continuous suction and disposal of liquids, dirty water or similar. Power: min. 230 V / 1,200 W Container: min. 45 l capacity with integrated residual emptying/drain for complete emptying of the container, sturdy chassis, compact dimensions with detachable handle, connection C-Storz coupling, water suction capacity of 133 l/min, slurping operation possible, sewage pump 230 l/min with a maximum solid size 30 mm, max. discharge head 8 m, dry-running safe, automatic-mechanical shut-off when maximum tank volume is reached, plug protection class IP 68, personal protection switch.

Suction hose \varnothing 38 mm, 10 m; drain hose \varnothing 38 mm, 10 m; 2-part suction pipe; aluminium floor nozzle 45 cm wide.

OPTIONAL ACCESSORIES

PRCD-S+ personal protection switch, ball valve with C-Storz-coupling

TECHNICAL DATA HYDRA-BOY

Main voltage	220-240 V / 50 Hz
Socket	max. 1,600 W
Sound pressure level	82 db(A)
Suction capacity	8,000 l/h
Container material	Plastic PP
Container volume	45 Liter
Power cable length	10 m
Suction hose length	10 m
Drain hose length	10 m
Suction hose	\varnothing 38 mm
Drain hose	\varnothing 38 mm
Weight	18 kg
Size without handle (B x T x H)	46x49x64 cm
Size with handle (B x T x H)	46x66x85 cm



TECHNICAL DATA TURBINE

Main voltage	220-240 V / 50 Hz
Turbine capacity	1,200 W
Volume flow / air volume	60 l/sec
Max. vacuum	230 mbar

TECHNICAL DATA PUMP

Main voltage	220-240 V / 50 Hz
Capacity waste water pump	900 W
Output pump	14,000 l/h
Discharge head, max.	8 m (0.8 bar)
Material	Plastic

Subject to technical changes, our terms and conditions apply: www.roessle.ag

rössle

Vacuum cleaners for fire departments